

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 March 2005 (24.03.2005)


PCT

(10) International Publication Number
WO 2005/026747 A3

- (51) International Patent Classification⁷: **H01L 21/66** (74) Agent: APPELFELD ZER LAW OFFICE; 29 Lilinblum, 65133 Tel-aviv (IL).
- (21) International Application Number: PCT/IL2004/000842 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 14 September 2004 (14.09.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/502,941 16 September 2003 (16.09.2003) US
- (71) Applicants and
(72) Inventors: GITMAN, Jacob [IL/IL]; 11/14 Haym Laskov st., 76654 Rehovot (IL). DANKNER, Yair [IL/IL]; 8 Hazerot Hadar St., 44359 Kfar Saba (IL). PIKARY, Yizhak [IL/IL]; 18b Hasahlav st., 42207 Netanya (IL).
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: ELECTRIC ULTIMATE DEFECTS ANALYZER DETECTING ALL DEFECTS IN PCB/MCM



(57) Abstract: A system for electric testing PCB/MCM before and after assembly. The system uses energy taken from a heating source, timely applied at certain ports of the PCB/MCM (entry ports). The energy is defused through the board inner layer tracks terminating at the end of the channel tracks of the PCB/MCM (exit ports). The rate of energy diffusion on the board is measured at the terminating ports in the time domain. The thermal emission is measured by a spectrometer that conducts infrared scans and analyzes the PCBs energy spectrum. Measurements can be taken as discrete measurements or as integrated measurements. The measurements results are compared with the pre-memorized values of a group of patterns that represent respective golden board. Defect analysis is automatically achieved based on learned defect test patterns.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:

28 July 2005